

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 9/12/2018 Revision date: 10/30/2024 Supersedes: 10/7/2021

SECTION 1: Identification	
1.1. Identification	
Product form Product name CAS-No. Product code Formula Other means of identification	 Mixture Maxline 13A Mixture 7452 Was TL0846 Bonded Magnesis Carbon Brisk
1.2. Recommended use and restrictions on	: Resin Bonded, Magnesia-Carbon Brick
Use of the substance/mixture	: Refractory Brick
Recommended use	: Industrial use
1.3. Supplier	
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 SDS@RescoProducts.com - WWW.RescoProducts.com	<u>om</u>
1.4. Emergency telephone number	
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Outside USA & Canada +1 703-741-5970
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mixtu	re
GHS US classification	
Germ cell mutagenicity Category 1B Carcinogenicity Category 1A Full text of H statements : see section 16	H340May cause genetic defectsH350May cause cancer
2.2. GHS Label elements, including precauti	onary statements
GHS US labeling Hazard pictograms (GHS US)	
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	 Danger H340 - May cause genetic defects H350 - May cause cancer P202 - Do not handle until all safety precautions have been read and understood.
	P280 - Wear Safety shoes, protective clothing, eye protection, protective gloves. P261 - Sawing or tear out operations- Avoid breathing dust.
2.3. Other hazards which do not result in cla	
No additional information available	
2.4. Unknown acute toxicity (GHS US)	
No additional information available	
SECTION 3: Composition/Information o	n ingredients
3.1. Substances	
Not applicable	
3.2. Mixtures	
Name	Product identifier % GHS US classification
Magnesium Oxide	CAS-No.: 1309-48-4 75 – 95 Not classified
graphite	CAS-No.: 7782-42-5 5 – 10 Not classified
Phenolic Resin	CAS-No.: 108-95-2 1 – 5 Not classified
Aluminum - metal powder	CAS-No.: 7429-90-5 1 – 5 Not classified
Coal Tar Pitch Full text of hazard classes and H-statements : see se	CAS-No.: 65996-93-2 1 – 5 Muta. 1B, H340 Carc. 1A, H350

Safety Data Sheet

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Dust when sawing or tear out. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
First-aid measures after ingestion	and easy to do. Continue rinsing. : Rinse mouth. Get medical advice/attention if you feel unwell. Do not induce vomiting.
4.2. Most important symptoms and effects (a	
	: Danger of serious damage to health by prolonged exposure through inhalation.
symptoms	
Symptoms/effects after inhalation	: Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
	: Causes eye irritation.
4.3. Immediate medical attention and specia	I treatment, if necessary
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	media
	 Use extinguishing media appropriate for surrounding fire. In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chemi	cal
Fire hazard	Product will not burn, but does contain small quantities of chemicals which can generate toxic and/or irritating vapors when initially heated. Under fire conditions hazardous combustion products such as carbon monoxide may be generated.
5.3. Special protective equipment and preca	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measure	es
6.1. Personal precautions, protective equipment	nent and emergency procedures
6.1.1. For non-emergency personnel	
Protective equipment 6.1.2. For emergency responders	: Safety shoes. Safety glasses. Protective gloves.
Protective equipment	: Equip cleanup crew with proper protection.
6.2. Environmental precautions	
No additional information available	
6.3. Methods and material for containment a	nd cleaning up
For containment	: Collect spillage.
Methods for cleaning up	: Collect spillage. Mechanically recover the product.
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid contact with
Hygiene measures	 skin and eyes. Do not breathe Dust when sawing or tear out. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
7.2. Conditions for safe storage, including a	о о
Storage conditions	: Store this product in a dry location where it can be protected from the elements.
	: Strong acids. Oxidizing agent.
SECTION 8: Exposure controls/persona	
8.1. Control parameters	
Maxline 13A (Mixture)	
No additional information available	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magnesium Oxide (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m ³ inhalable dust
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	10 mg/m ³ respirable dust
graphite (7782-42-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m3 (Poppirghlo fraction)
	2 mg/m ³ (Respirable fraction)
Phenolic Resin (108-95-2)	
No additional information available	
Coal Tar Pitch (65996-93-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.2 mg/m ³ (Coal tar pitch volatiles, as benzene soluble aerosol; USA; Time-weighted average
	exposure limit 8 h; TLV - Adopted Value)
Aluminum - metal powder (7429-90-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m3 (Pospirable fraction)
	1 mg/m ³ (Respirable fraction)
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Person	
Personal protective equipment:	a procession of a la familia and
Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Safety shoes. Wear suitable protective clothing	
Respiratory protection:	
Dust when sawing or tear out. Wear appropriate mas	sk
SECTION 9: Physical and chemical pro	perties
9.1. Information on basic physical and cher	nical properties
Physical state	: Solid
Appearance	: Solid in various shapes.
Color	: Black
Odor	: Resin Odor
Odor threshold	: No data available
pH	: No data available
Melting point	: > 2800 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
• •	: No data available
Relative vapor density at 20°C	
Relative vapor density at 20°C Relative density	: ≈ 2.9
Relative vapor density at 20 C Relative density Solubility	
Relative density Solubility	: ≈2.9
Relative density	: ≈ 2.9 : Insoluble in water.
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature	: ≈ 2.9 : Insoluble in water. : No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature	 ≈ 2.9 Insoluble in water. No data available No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic	 ≈ 2.9 Insoluble in water. No data available No data available No data available No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 ≈ 2.9 Insoluble in water. No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits	 ≈ 2.9 Insoluble in water. No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 ≈ 2.9 Insoluble in water. No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties	 ≈ 2.9 Insoluble in water. No data available
Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties	 ≈ 2.9 Insoluble in water. No data available

No additional information available

Safety Data Sheet

SECTION 10: Stability and reactivity	
10.1. Reactivity	
May release smoke when heated. Combustion products	s include carbon monoxide, carbon dioxide, and hydrocarbon vapors.
10.2. Chemical stability	
Stable under normal conditions.	
10.3. Possibility of hazardous reactions	
No additional information available	
10.4. Conditions to avoid	
No additional information available	
10.5. Incompatible materials	
No additional information available	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral) : Acute toxicity (dermal) :	Not classified Not classified
Acute toxicity (inhalation) :	Not classified
Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
graphite (7782-42-5)	
LD50 oral rat	> 2000 mg/kg (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
LC50 Inhalation - Rat	> 2000 mg/m ³ air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (dust))
Coal Tar Pitch (65996-93-2)	
LD50 oral rat	> 15000 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Skin corrosion/irritation :	Not classified
Magnesium Oxide (1309-48-4)	
	11 (10 %)
pH	11 (10 %)
graphite (7782-42-5)	
рН	7 (1.3 %)
Serious eye damage/irritation :	Not classified
Magnesium Oxide (1309-48-4)	
рН	11 (10 %)
graphite (7782-42-5)	
рН	7 (1.3 %)
Respiratory or skin sensitization :	Not classified
Germ cell mutagenicity :	May cause genetic defects.
Carcinogenicity : Phenolic Resin (108-95-2)	May cause cancer.
IARC group	3 - Not classifiable
Coal Tar Pitch (65996-93-2)	
IARC group	1 - Carcinogenic to humans

Safety Data Sheet

Reproductive toxicity STOT-single exposure	: Not classified : Not classified
STOT-repeated exposure Aspiration hazard	: Not classified : Not classified
Viscosity, kinematic	: No data available
Magnesium Oxide (1309-48-4)	
Viscosity, kinematic	Not applicable (solid)
Potential Adverse human health effects and	: Danger of serious damage to health by prolonged exposure through inhalation.
symptoms Symptoms/effects after inhalation	: Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact Symptoms/effects after eye contact	Causes skin irritation. Causes eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
graphite (7782-42-5)	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Behaviour)
EC50 72h - Algae [1]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
EC50 72h - Algae [2]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Cell numbers)
Coal Tar Pitch (65996-93-2)	
LC50 - Fish [1]	128 mg/l (LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pagrus major; Semi-static system; Salt water; Experimental value)
EC50 - Crustacea [1]	> 100 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 - Fish [2]	100-1000,LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oryzias latipes; Semi-static system; Fresh water; Experimental value
Threshold limit - Algae [1]	220 mg/l (EL50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)
12.2. Persistence and degradability	
Magnesium Oxide (1309-48-4)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
graphite (7782-42-5)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Coal Tar Pitch (65996-93-2)	
Persistence and degradability	No test data available. Adsorbs into the soil.
Aluminum - metal powder (7429-90-5)	
Persistence and degradability	Biodegradability in soil: not applicable.

Safety Data Sheet

Aluminum - metal powder (7429-90-5)	
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
12.3. Bioaccumulative potential	
Magnesium Oxide (1309-48-4)	Ne biogenum deter dete susileble
Bioaccumulative potential	No bioaccumulation data available.
graphite (7782-42-5)	
Bioaccumulative potential	Not bioaccumulative.
Coal Tar Pitch (65996-93-2)	
Bioaccumulative potential	No test data available.
Aluminum - metal powder (7429-90-5)	
Bioaccumulative potential	No test data of component(s) available.
12.4. Mobility in soil	
Magnesium Oxide (1309-48-4)	
Surface tension	No data available in the literature
Ecology - soil	No data available.
Coal Tar Pitch (65996-93-2)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	Koc,12600-800000; Calculated value; log Koc; 4.1-5.9; Calculated value
Aluminum - metal powder (7429-90-5)	
Ecology - soil	Contains component(s) that adsorb(s) into the soil.
12.5. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	
13.1. Disposal methods	Disease is a sefer measure is assertioned with level/setimal regulations
Product/Packaging disposal recommendations : SECTION 14: Transport information	Dispose in a safe manner in accordance with local/national regulations.
In accordance with DOT / TDG / IMDG / IATA	
Department of Transportation (DOT)	
In accordance with DOT Not regulated	
Transportation of Dangerous Goods	
Not regulated Transport by sea	
Not regulated	
Air transport Not regulated	
SECTION 15: Regulatory information	
15.1. US Federal regulations	
Maxline 13A (Mixture)	
Note	This information must be included in all SDS's that are copied and distributed for this material.
(TSCA) inventory, except for:	s Active on the United States Environmental Protection Agency Toxic Substances Control Act
Aluminum - metal powder	CAS-No. 7429-90-5 1 – 5%
Phenolic Resin (108-95-2)	
Subject to reporting requirements of United States SAF Listed on EPA Hazardous Air Pollutant (HAPS)	RA Section 313

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phenolic Resin (108-95-2)	
CERCLA RQ	1000 lb
RQ (Reportable quantity, section 304 of EPA's List of	1000 lb
Lists)	
SARA Section 302 Threshold Planning Quantity	10000 lb 500lb if the substance is solid in powder form with particle size less than 100 microns,
(TPQ)	or is in solution or molten form
Aluminum - metal powder (7429-90-5)	
Note	This information must be included in all SDS's that are copied and distributed for this material.
15.2. International regulations	
CANADA	
Magnesium Oxide (1309-48-4)	.0
Listed on the Canadian DSL (Domestic Substances Lis	st)
graphite (7782-42-5)	A
Listed on the Canadian DSL (Domestic Substances Lis	st)
Phenolic Resin (108-95-2)	
Listed on the Canadian DSL (Domestic Substances Lis	st)
Coal Tar Pitch (65996-93-2)	
Listed on the Canadian DSL (Domestic Substances Lis	st)
EU-Regulations	
No additional information available	
National regulations	
Coal Tar Pitch (65996-93-2)	
Listed on IARC (International Agency for Research on	Cancer)
15.3. US State regulations	
Maxline 13A (Mixture)	
U.S California - Proposition 65 - Other information	This product contains coal tar pitch, a chemical known to the State of California to cause
0.3 California - Proposition 65 - Other Information	cancer. For more information go to WWW.P65Warnings.ca.gov
	cancer. For more information go to www.r oowarnings.ca.gov
Component	State or local regulations
Magnesium Oxide (1309-48-4)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
Magnesium Oxide (1503-40-4)	Substance List; U.S Pennsylvania - RTK (Right to Know) List
Graphite (7782-42-5)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List
Phenolic Resin 108-95-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List
Coal Tar Pitch (65996-93-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List
SECTION 16: Other information	
according to Federal Register / Vol. 77, No. 58 / Monda	av. March 26, 2012 / Rules and Regulations
Revision date :	10/30/2024
Other information :	Report language name. English. In the event of any conflict between English and other language
	versions, the English version shall prevail.
Full text of H-phrases	
H340 May cause genetic defects	

Full text of H-phrases	
H340	May cause genetic defects
H350	May cause cancer
Safety Data Sheet (SDS) LISA	

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.