

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/26/2015 Revision date: 8/7/2024 Supersedes: 7/28/2021

SECTION 1: Identification						
1.1. Identification						
Product form Product name CAS-No. Product code Other means of identification	 Mixture Rescocast 17AC Coarse Mixture 0463 Alumina Cement Bonded Castable 					
1.2. Recommended use and restrictions on						
Use of the substance/mixture	: Refractory					
Recommended use	: Industrial use					
1.3. Supplier Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 SDS@RescoProducts.com - WWW.RescoProducts.	<u>com</u>					
1.4. Emergency telephone number						
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Outside USA & Canada +1 703-741-5970					
SECTION 2: Hazard(s) identification						
2.1. Classification of the substance or mixt	Jre					
GHS US classification Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H315Causes skin irritationH320Causes eye irritationH350May cause cancer (Inhalation)					
2.2. GHS Label elements, including precaut	ionary statements					
GHS US labeling Hazard pictograms (GHS US) Signal word (GHS US) Hazard statements (GHS US)	: Danger : H315 - Causes skin irritation H320 - Causes eye irritation H350 - May cause cancer (Inhalation)					
Precautionary statements (GHS US)	 P280 - Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P260 - Do not breathe dust/fume/gas/mist/vapors/spray. 					
2.3. Other hazards which do not result in cl						
No additional information available						
2.4. Unknown acute toxicity (GHS US)						
No additional information available						
SECTION 3: Composition/Information of	on ingredients					
3.1. Substances						
Not applicable						
3.2. Mixtures						
Name	Product identifier % GHS US classification					
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1 75 – 95 Not classified					
Calcium Aluminate Cement	CAS-No.: 65997-16-2 10 – 20 Skin Irrit. 2, H315 Eye Irrit. 2B, H320					
cristobalite Full text of hazard classes and H-statements : see si	CAS-No.: 14464-46-1 0.1 – 0.5 Carc. 1A, H350					

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures					
4.1. Description of first aid measures					
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).				
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.				
First-aid measures after skin contact	: Gently wash with plenty of soap and water.				
First-aid measures after eye contact	 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if preser and easy to do. Continue rinsing. 				
First-aid measures after ingestion	: Rinse mouth. Get medical advice/attention if you feel unwell. Do not induce vomiting.				
4.2. Most important symptoms and effects					
Potential Adverse human health effects and	: Danger of serious damage to health by prolonged exposure through inhalation.				
symptoms Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May caus cancer by inhalation.				
Symptoms/effects after skin contact	: Causes skin irritation.				
Symptoms/effects after eye contact	: Causes eye irritation.				
4.3. Immediate medical attention and spec	ial treatment, if necessary				
No additional information available					
SECTION 5: Fire-fighting measures					
5.1. Suitable (and unsuitable) extinguishing	g media				
Suitable extinguishing media Unsuitable extinguishing media	 Use extinguishing media appropriate for surrounding fire. In case of fire, all extinguishing media allowed. 				
5.2. Specific hazards arising from the chem	nical				
Fire hazard	: Not flammable.				
5.3. Special protective equipment and prec	cautions for fire-fighters				
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Prevent entry to sewers and				
Protection during firefighting	public waters. Do not enter fire area without proper protective equipment, including respiratory protection.				
SECTION 6: Accidental release measu					
6.1. Personal precautions, protective equip					
6.1.1. For non-emergency personnel	A sold and the second second second				
Protective equipment 6.1.2. For emergency responders	: Avoid creating or spreading dust.				
Protective equipment	: Equip cleanup crew with proper protection.				
6.2. Environmental precautions					
Prevent entry to sewers and public waters.					
6.3. Methods and material for containment	and cleaning up				
For containment	: Collect spillage.				
Methods for cleaning up	: On land, sweep or shovel into suitable containers.				
6.4. Reference to other sections					
No additional information available					
SECTION 7: Handling and storage					
7.1. Precautions for safe handling					
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust.				
Hygiene measures	 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. 				
7.2. Conditions for safe storage, including					
Storage conditions Incompatible products	 Store this product in a dry location where it can be protected from the elements. Strong bases. Strong acids. 				
SECTION 8: Exposure controls/person	al protection				
8.1. Control parameters					
8.1. Control parameters Rescocast 17AC Coarse (Mixture) No additional information available					

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ respirable dust
Calcium Aluminate Cement (65997-16-2)	
No additional information available	
cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA	0.025 mg/m ³ respirable dust
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
8.2. Appropriate engineering controls	
	: Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Persona	
Personal protective equipment:	
Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
SECTION 9: Physical and chemical prop	perties
0.4 Information on basis physical and show	ical properties
9.1. Information on basic physical and chem	
Physical state	: Solid
Physical state Appearance Color Odor	 Solid Granular mixture. Off-white odorless
Physical state Appearance Color Odor Odor threshold	 Solid Granular mixture. Off-white odorless No data available
Physical state Appearance Color Odor Odor threshold pH	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5
Physical state Appearance Color Odor Odor threshold pH pH solution concentration	 Solid Granular mixture. Off-white odorless No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available No data available No data available No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1)	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available No data available No data available No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available Zo data available No data available No data available Zo data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available So data available<
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits	: Solid : Granular mixture. : Off-white : odorless : No data available : ≈ 10.5 : 10 % : > 3000 °F : No data available : ≈ 2.6 : Slightly soluble in water. : No data available : No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information No additional information available	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information No additional information available	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available
Physical state Appearance Color Odor Odor threshold pH pH solution concentration Melting point Freezing point Boiling point Flash point Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) Vapor pressure Relative vapor density at 20°C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature Decomposition temperature Viscosity, kinematic Viscosity, dynamic Explosion limits Explosive properties Oxidizing properties 9.2. Other information No additional information available SECTION 10: Stability and reactivity	 Solid Granular mixture. Off-white odorless No data available ≈ 10.5 10 % > 3000 °F No data available

Stable under normal conditions.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions					
No additional information available					
10.4. Conditions to avoid					
No additional information available					
10.5. Incompatible materials					
No additional information available					
10.6. Hazardous decomposition products					
No additional information available					
SECTION 11: Toxicological information					
11.1. Information on toxicological effects					
	Not classified				
Acute toxicity (dermal) :	Not classified				
Acute toxicity (inhalation) :	Not classified				
aluminium oxide, non-fibrous (1344-28-1)					
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))				
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))				
Skin corrosion/irritation :	Causes skin irritation. pH: ≈ 10.5				
aluminium oxide, non-fibrous (1344-28-1)					
рН	9 – 10.5 (aqueous suspension, 33 %)				
Calcium Aluminate Cement (65997-16-2)					
рН	≤ 13				
cristobalite (14464-46-1)					
рН	6 - 7				
Serious eye damage/irritation :	Causes eye irritation. pH: ≈ 10.5				
aluminium oxide, non-fibrous (1344-28-1)					
рН	9 – 10.5 (aqueous suspension, 33 %)				
Calcium Aluminate Cement (65997-16-2)					
рН	≤ 13				
cristobalite (14464-46-1)					
рН	6 – 7				
Respiratory or skin sensitization :	Not classified				
Germ cell mutagenicity :	Not classified				
Carcinogenicity :	May cause cancer (Inhalation).				
Reproductive toxicity :	Not classified				
STOT-single exposure :	Not classified				
STOT-repeated exposure :	Not classified				
Aspiration hazard : Viscosity, kinematic :	Not classified No data available				
aluminium oxide, non-fibrous (1344-28-1)					
Viscosity, kinematic	Not applicable (solid)				
Potential Adverse human health effects and :	Danger of serious damage to health by prolonged exposure through inhalation.				
symptoms Symptoms/effects after inhalation :	Danger of serious damage to health by prolonged exposure through inhalation. May cause				
	cancer by inhalation.				
Symptoms/effects after skin contact : Symptoms/effects after eye contact :	Causes skin irritation. Causes eye irritation.				

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information					
12.1. Toxicity					
aluminium oxide, non-fibrous (1344-28-1)					
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)				
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)				
12.2. Persistence and degradability					
aluminium oxide, non-fibrous (1344-28-1)					
Persistence and degradability	Not applicable.				
Chemical oxygen demand (COD)	Not applicable				
ThOD	Not applicable				
cristobalite (14464-46-1)					
Persistence and degradability	Mineral. Not applicable.				
Chemical oxygen demand (COD)	Not applicable				
ThOD	Not applicable				
BOD (% of ThOD)	Not applicable				
12.3. Bioaccumulative potential					
aluminium oxide, non-fibrous (1344-28-1)					
Bioaccumulative potential	No data available.				
cristobalite (14464-46-1)					
Bioaccumulative potential	No data available.				
12.4. Mobility in soil					
aluminium oxide, non-fibrous (1344-28-1)					
Surface tension	No data available in the literature				
Ecology - soil	No data available.				
cristobalite (14464-46-1)					
Ecology - soil	No data available.				
12.5. Other adverse effects					
No additional information available					
SECTION 13: Disposal considerations					
13.1. Disposal methods					
Product/Packaging disposal recommendations : SECTION 14: Transport information	Dispose in a safe manner in accordance with local/national regulations.				
In accordance with DOT / TDG / IMDG / IATA Department of Transportation (DOT) In accordance with DOT Not regulated Transportation of Dangerous Goods Not regulated Transport by sea Not regulated Air transport Not regulated					
SECTION 15: Regulatory information					
15.1. US Federal regulations					
——————————	s Active on the United States Environmental Protection Agency Toxic Substances Control Act				

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Not subject to repor	ting requirements of the	e United Stat	tes SARA Section 313						
Note		Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.							
5.2. Internationa	I regulations								
ANADA									
luminium oxide	, non-fibrous (1344	-28-1)							
isted on the Canac	lian DSL (Domestic Sul	bstances Lis	st)						
Calcium Alumina	ate Cement (65997-	16-2)							
	lian DSL (Domestic Sul		it)						
cristobalite (144	64-46-1)								
	lian DSL (Domestic Sul	bstances Lis	t)						
U-Regulations lo additional informa lational regulation lo additional informa	S								
5.3. US State reg	gulations								
Rescocast 17AC	Coarse (Mixture)								
	oposition 65 - Other in	formation	tion This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov						
cristobalite (144	64-46-1)								
J.S California - Proposition 65 - Carcinogens List	U.S Californi Proposition 65 Developmenta	-	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)			
Yes	No		No	No					
					·	· · · · · · · · · · · · · · · · · · ·			
Component	(10.11.00.1)		State or local regulations						
aluminium oxide, non-fibrous (1344-28-1)			U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List						
Cristobalite (14464-46-1)		U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List							
	ther information								
ccording to Federal Revision date Other information		:	y, March 26, 2012 / Rule 8/7/2024 Report language name. versions, the English ve	English. In the event of	any conflict between E	English and other langu			
	Causes skin irritation								
1315				Causes eye irritation					
1320									