

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/15/2015 Revision date: 8/6/2024 Supersedes: 7/19/2021

SECTION 1: Identification			
1.1. Identification			
Product form Product name CAS-No. Product code Other means of identification	 Mixture Rescocast 3PC Mixture 0518 Alumina-Silicate Cement Bonded Castable 		
1.2. Recommended use and restrictions of			
Use of the substance/mixture	: Refractory		
Recommended use	: Industrial use		
1.3. Supplier			
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 <u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts</u>	<u>s.com</u>		
1.4. Emergency telephone number			
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Outside USA & Canada +1 703-741-5970		
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance or mix			
GHS US classification			
Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H315Causes skin irritationH320Causes eye irritationH350May cause cancer (Inhalation)		
2.2. GHS Label elements, including precau	itionary statements		
GHS US labeling Hazard pictograms (GHS US)			
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	H320 - Causes eye irritation H350 - May cause cancer (Inhalation)		
2.3. Other hazards which do not result in a	lassification		
No additional information available			
2.4. Unknown acute toxicity (GHS US) No additional information available			
SECTION 3: Composition/Information	on ingredients		
3.1. Substances			
a. L. audstadices			
Not applicable			
Not applicable 3.2. Mixtures	Product identifier % GHS US classification		
	Product identifier % GHS US classification CAS-No.: 65997-16-2 20 – 50 Skin Irrit. 2, H315 Eve Irrit. 2B H320		
Not applicable 3.2. Mixtures Name			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice
First-aid measures after inhalation	(show the label where possible).Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
First-aid measures after ingestion	and easy to do. Continue rinsing. : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects	
Potential Adverse human health effects and	: Danger of serious damage to health by prolonged exposure through inhalation.
symptoms	
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
4.3. Immediate medical attention and speci	al treatment, if necessary
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	g media
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media 5.2. Specific hazards arising from the chem	: In case of fire, all extinguishing media allowed.
Fire hazard	: Not flammable.
5.3. Special protective equipment and prec	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measure	res
6.1. Personal precautions, protective equip	ment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures 6.1.2. For emergency responders	: Do not breathe dust. Avoid contact with skin and eyes.
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment	and cleaning up
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimize generation of dust.
6.4. Reference to other sections	
See Heading 8. Exposure controls and personal pro	tection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust.
Hygiene measures	Avoid contact with skin and eyes. Do not breathe dust. : Wash hands and other exposed areas with mild soap and water before eating, drinking or
	smoking and when leaving work.
7.2. Conditions for safe storage, including	
Storage conditions Incompatible products	 Store this product in a dry location where it can be protected from the elements. Strong bases. Strong acids.
SECTION 8: Exposure controls/person	
8.1. Control parameters	
Rescocast 3PC (Mixture)	
No additional information available	
Calcium Aluminate Cement (65997-16-2)	
No additional information available	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m ³ respirable dust
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m3 (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -
	Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Persona	
Personal protective equipment: Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask	
Other information: Do not eat, drink or smoke during use.	
SECTION 9: Physical and chemical prop	perties
9.1. Information on basic physical and chem	nical properties
Physical state	: Solid
Appearance	: Granular mixture.
Color	: brown
Odor Odor threshold	: earthy : No data available
pH	$\therefore \approx 10.5$
pH solution concentration	. ≈ 10.5 : 10 %
Melting point	: > 2000 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈ 0.9
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow) Auto-ignition temperature	: No data available : No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not Applicable
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
	: No data available

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
	Not classified
Acute toxicity (dermal) : Acute toxicity (inhalation) :	Not classified
	Causes skin irritation.
	pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
pH	≤ 13
cristobalite (14464-46-1)	
pH	6-7
quartz (14808-60-7)	
рН	6-7
Serious eye damage/irritation :	c Causes eye irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
pH	≤ 13
cristobalite (14464-46-1)	
pH	6-7
quartz (14808-60-7)	
рН	6-7
	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	May cause cancer (Inhalation).
quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity : STOT-single exposure :	Not classified
STOT-repeated exposure :	Not classified
Aspiration hazard	Not classified
Viscosity, kinematic	Not Applicable
Potential Adverse human health effects and symptoms	Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation :	Danger of serious damage to health by prolonged exposure through inhalation. May cause
Symptoms/effects after skin contact	cancer by inhalation.
	Causes eye irritation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 42. Eacle sized information	
SECTION 12: Ecological information	
12.1. Toxicity No additional information available	
12.2. Persistence and degradability	
Rescocast 3PC (Mixture)	
Persistence and degradability	Not established.
cristobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Rescocast 3PC (Mixture)	
Bioaccumulative potential	Not established.
cristobalite (14464-46-1)	
Bioaccumulative potential	No data available.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
cristobalite (14464-46-1)	
Ecology - soil	No data available.
12.5. Other adverse effects	
5	None known No other effects known.
SECTION 13: Disposal considerations	
13.1. Disposal methods	
	Dispose in a safe manner in accordance with local/national regulations.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA Department of Transportation (DOT) In accordance with DOT Not regulated Transportation of Dangerous Goods	
Not regulated Transport by sea Not regulated	
Air transport Not regulated	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Rescocast 3PC (Mixture)

U.S. - California - Proposition 65 - Other information This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-46-	-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

quartz (14808-60-7)					
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity	, ,	, , , , , , , , , , , , , , , , , , ,
Ŭ	. ,	- Female	- Male		
Yes	No	No	No		

Component	State or local regulations	
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous	
Clistobalite (14404-40-1)	Substance List; U.S Pennsylvania - RTK (Right to Know) List	
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List	
SECTION 16: Other informati	on	
according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
Revision date	: 8/6/2024	
Other information	: Report language name. English. In the event of any conflict between English and other language	

versions, the English version shall prevail.		
Full text of H-phrases		
H315	Causes skin irritation	
H320	Causes eye irritation	
H350	May cause cancer	

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.