

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/1/2015 Revision date: 12/13/2024 Supersedes: 12/30/2021

SECTION 1: Identification				
1.1. Identification				
Product form	: Mixture			
Product name	: Unicrete 85LC			
CAS-No.	: Mixture			
Product code	: 3149 : Alumina-Silicate Cement Bonded Castable			
Other means of identification 1.2. Recommended use and restrictions or		Jement Bonded Cast	lable	
Use of the substance/mixture	: Refractory			
Recommended use	: Industrial use			
1.3. Supplier				
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 <u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts</u>	<u>.com</u>			
1.4. Emergency telephone number				
Emergency number		NLY (CHEMTREC) U		0-424-9300
SECTION 2: Hazard(s) identification	Outside USA & Ca	anada +1 703-741-59	970	
2.1. Classification of the substance or mix	ture			
GHS US classification Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H	320 Cause	es skin irritation es eye irritation ause cancer (Inhala	ation)
2.2. GHS Label elements, including precau	tionary statements	5		
GHS US labeling Hazard pictograms (GHS US)				
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	: P280 - Wear eye P305+P351+P338 contact lenses, if J P332+P313 - If sk P337+P313 - If ey	ve irritation e cancer (Inhalation) protection, Dust resp 8 - IF IN EYES: Rinse present and easy to o kin irritation occurs: G ye irritation persists: 0	e cautiously with wa do. Continue rinsing det medical advice/	ater for several minutes. Remove g. attention.
2.3. Other hazards which do not result in c	P260 - Do not bre	athe dust.		
No additional information available	assingation			
2.4. Unknown acute toxicity (GHS US)				
No additional information available				
SECTION 3: Composition/Information	on ingradiants			
3.1. Substances				
Not applicable				
3.2. Mixtures				
Name		Product identi	fier %	GHS US classification
aluminium oxide, non-fibrous		CAS-No.: 1344-2		Not classified
Calcium Aluminate Cement		CAS-No.: 65997-	16-2 5 – 10	Skin Irrit. 2, H315
auo ta		CAC No : 44000	60745	Eye Irrit. 2B, H320
quartz		CAS-No.: 14808-		Carc. 1A, H350
cristobalite		CAS-No.: 14464-	46-1 0.5 – 1	Carc. 1A, H350

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*** DRAFT ***

Full text of hazard classes and H-statements : see set	ction 16
SECTION 4: First-aid measures	
4.1. Description of first aid measures	
	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after skin contact First-aid measures after eye contact	 Allow affected person to breathe fresh air. Allow the victim to rest. Gently wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects (a	
	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact 4.3. Immediate medical attention and specia	: Causes eye irritation.
A.S. Infinediate medical attention and Special No additional information available	r ucament, in Neucosary
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	
Unsuitable extinguishing media	 Use extinguishing media appropriate for surrounding fire. In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chemi	
	: Not flammable.
5.3. Special protective equipment and preca	
	: Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from entering environment.
Protection during firefighting SECTION 6: Accidental release measure	: Do not enter fire area without proper protective equipment, including respiratory protection.
6.1. Personal precautions, protective equipn	nent and emergency procedures
	: Do not breathe dust. Avoid contact with skin and eyes.
6.1.2. For emergency responders Protective equipment	: Equip cleanup crew with proper protection.
	: Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment a	nd cleaning up
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimize generation of dust.
6.4. Reference to other sections	
See Heading 8. Exposure controls and personal prote	ection.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eyes. Do not breathe dust. Wash hands and other exposed areas with mild soap and water before eating, drinking or
	smoking and when leaving work.
7.2. Conditions for safe storage, including a	
	 Store this product in a dry location where it can be protected from the elements. Strong bases. Strong acids.
SECTION 8: Exposure controls/persona	
8.1. Control parameters	
cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



	viarch 20, 2012 / Rules and Regulations
cristobalite (14464-46-1)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	0.05 mg/m ³ respirable dust
aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL TWA	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
Appropriate engineering controls	: Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Person	nal protective equipment
Personal protective equipment:	
Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection: Wear appropriate mask	
Other information: Do not eat, drink or smoke during use.	
	a na anta a
SECTION 9: Physical and chemical pro	operties
9.1. Information on basic physical and che	mical properties
Physical state	: Solid
Appearance	: Granular mixture.
Color	: Gray
Odor Odor threshold	: earthy
Odor threshold	: No data available
pH pH solution concentration	: ≈ 10.5 : 10 %
Melting point	: > 2500 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈2.3
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic Viscosity, dynamic	: Not Applicable : No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
9.2. Other information	
No additional information available	

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*** DRAFT ***

SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
	Not classified
Acute toxicity (dermal) : Acute toxicity (inhalation) :	Not classified Not classified
aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation :	Causes skin irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 - 7
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 – 7
Serious eye damage/irritation :	Causes eye irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 - 7
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 – 7
Respiratory or skin sensitization :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	May cause cancer (Inhalation).

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



quartz (14808-60-7)			
IARC group	1 - Carcinogenic to humans		
	Not classified		
	Not classified		
STOT-repeated exposure : Aspiration hazard :	Not classified Not classified		
Viscosity, kinematic	Not Applicable		
aluminium oxide, non-fibrous (1344-28-1)			
Viscosity, kinematic	Not applicable (solid)		
Potential Adverse human health effects and : symptoms	Danger of serious damage to health by prolonged exposure through inhalation.		
Symptoms/effects after inhalation :	Danger of serious damage to health by prolonged exposure through inhalation. May cause		
Symptoms/effects after skin contact :	cancer by inhalation. Causes skin irritation.		
Symptoms/effects after eye contact :	Causes eye irritation.		
SECTION 12: Ecological information			
12.1. Toxicity			
aluminium oxide, non-fibrous (1344-28-1)			
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)		
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)		
12.2. Persistence and degradability			
Unicrete 85LC (Mixture)			
Persistence and degradability	Not established.		
Calcium Aluminate Cement (65997-16-2)			
Persistence and degradability	Rapidly degradable		
cristobalite (14464-46-1)			
Persistence and degradability	Mineral, Not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
BOD (% of ThOD)	Not applicable		
aluminium oxide, non-fibrous (1344-28-1)			
Persistence and degradability	Not applicable.		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
quartz (14808-60-7)			
Persistence and degradability	Not applicable.		
Biochemical oxygen demand (BOD)	Not applicable		
Chemical oxygen demand (COD)	Not applicable		
ThOD	Not applicable		
12.3. Bioaccumulative potential			
Unicrete 85LC (Mixture)			
Bioaccumulative potential	Not established.		
cristobalite (14464-46-1)			
Bioaccumulative potential	No data available.		
<u> </u>	1		

Safety Data Sheet

aluminium oxide, non-f Bioaccumulative potential quartz (14808-60-7) Bioaccumulative potential 12.4. Mobility in soil cristobalite (14464-46-1

aluminium oxide, non-f

Ecology - soil

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

fibrous (1344-28-1)		
	No data available.	
	No data available.	
1)		
	No data available.	
-fibrous (1344-28-1)		
	No data available in the literature	

Surface tension	No data available in the literature
Ecology - soil	No data available.
12.5. Other adverse effects	
Effect on the global warming	: None known
SECTION 13: Disposal considerations	
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA Department of Transportation (DOT)	
In accordance with DOT	
Not regulated	
Transportation of Dangerous Goods	

Transportation of Dangerous Goo Not regulated Transport by sea Not regulated Air transport Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

Calcium Aluminate Cement (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

*** DRAFT ***

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*** DRAFT ***

National regulations	
quartz (14808-60-7)	
Listed on IARC (International Agency for Research on	Cancer)
15.3. US State regulations	
Unicrete 85LC (Mixture)	
U.S California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause
	cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-46-	1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
		- Female	- Male		
Yes	No	No	No		

quartz (14808-60-7)					
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
_		- Female	- Male		
Yes	No	No	No		

Component	State or local regulations
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous
	Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List
SECTION 16: Other information	

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date Other information : 12/13/2024 : Report language name. English. In the event of any conflict between English and other language

versions, the English version shall prevail.

Full text of hazard classes and H-statementsH315Causes skin irritationH320Causes eye irritation

H350 May cause cancer

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.